

FUJITSU Image Scanner fi-7030

Evolved entry model suitable for quick scanning



shaping tomorrow with you

fi-7030 Features

Ideal for desktop scanning with its compact size and card scanning capability

The fi-7030 handles the scanning of a wide range of documents reliably from documents to thick documents (40-209g/m²), and plastic cards including embo cards. Long paper scanning of up to 5 meters and over is also available as we A3 size scanning with a carrier sheet that comes with the scanner as an opt

- •Compact design allowing it to be placed anywhere
- Its noticeable compact size with a sophisticated design suits various environments. The scanner fits in small spaces even smaller than spaces that are A4 in size on a desk.
- •Fast processing performance The fi-7030 scans at a speed of 27 ppm / 54 ipm (A4, portrait, Color, 200 / 300 dpi), which is increased by 35% compared to the previous model. The scanner will not make you or your customers wait with a quick startup time of half a second and a recovery time of 1.0 seconds after resuming from sleep mode.
- •Accurate mixed batch scanning for different types of documents The Skew Reducer prevents the following documents from being skewed when the preceding document is skewed, thus preventing the image from being incomplete with missing parts even in the case of a batch scan with various types of documents. This also reduces the burden of re-scanning.



batch sca

Automatically creates the best suited image quality without has The PaperStream IP scanner driver, which supports TWAIN/ISIS, avoids the inconveni of fine adjustments to the settings for OCR processes. It automatically conv the images into exceptionally clean images, accelerating OCR even when scan wrinkled or soiled documents, or documents with a background pattern.

Advanced software for your work efficiency

- PaperStream Capture Image capture software
- With an intuitive interface, batch scanning with various capture feature PaperStream Capture allows you to incorporate information into your organizati workflow effectively and efficiently. By pre-setting a scanning profile, PaperStr Capture could help you simplify your workflow with easy scanning operation.
- Scanner Central Admin Centralized scanner management software Scanner Central Admin allows the administrator to manage a large number scanners in the network by delivering simultaneous driver updates and scar setup information, or monitoring consumable and error statuses via the netw

Option: Carrier Sheets

Carrier Sheets allow you to scan documents, photos or clippings larger than A4 size. Documents larger than A4 (such as A3 or B4) or photos and clippings that can be damaged easily can be digitized when using the A3 Carrier Sheet.



* Carrier Sheets (5 sheets per set) can be purchased separately. (The Carrier Sheet should be replaced approximately every 500 scans)

Description		
Supported operating systems		Windows® 10 (32-bit/64-bit), Windows® 8.1/8 (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows Vista® (32-bit/64-bit), Windows Server® 2016 (64-bit), Windows Server® 2012 R2 (64-bit), Windows Server® 2012 (64-bit), Windows Server® 2008 R2 (64-bit), Windows Server® 2008 (32-bit/64-bit)
Scanner type		ADF (Automatic Document Feeder)
Scanning mode	۱ <u>۲</u>	Simplex / Duplex, Color / Grayscale / Monochrome
Image sensor ty		Color CIS (Contact Image Sensor) x 2 (front x 1, back x 1)
Light source	/pc	3 Color LED (Red / Green / Blue) x 2 (front x 1, back x 1)
Multifeed detec	rtion	Ultrasonic multi-feed detection sensor x 1, Paper detection sensor x 1
	Maximum	216 x 355.6 mm (8.5 x 14 in.)
	Minimum	50.8 x 50.8 mm (2 x 2 in.)
Document size	Long page scanning (Maximum)*1	216 x 5,588 mm (8.5 x 220 in.)
-	Paper	40 to 209 g/m ² (11 to 56 lb), A8 size: 127 to 209 g/m ² (34 to 56 lb)
Paper weight (Thickness)	Plastic card	0.76 mm or less, Embossed card: usable, Multiple cards cannot be set at a time
Scanning speed	Color*3	
(A4 Portrait)*2	Grayscale*3	Simplex: 27 ppm (200/300 dpi), Duplex: 54 ipm (200/300 dpi)
(A4 Fordard)	Monochrome*4	
Paper chute cap	acity (A4 Portrait)*5	50 sheets (A4: 80 g/m ² or 20 lb)
Background col	lors	White
Optical resolution	ion	600 dpi
Output	Color (24-bit)	
resolution*6	Grayscale (8-bit)	50 to 600 dpi (adjustable by 1 dpi increments), 1,200 dpi (driver)*7
resolution	Monochrome (1-bit)	
	Color	24-bit
Output format	Grayscale	8-bit
	Monochrome	1-bit
Internal video p	processing	1,024 levels (10-bit)
Interface		USB 2.0 / USB 1.1
intenace		
Connector shap	e	Туре В
		Type B Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, De-Screen, Emphasis, Halftone, Dropout color (None /Red /Green /Blue /White / Saturation /Custom), sRGB output, Split image, De-Skew, Edge filler, Vertical streaks reduction, Cropping, Dither, Static threshold
Connector shap	ng functions	Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, De-Screen, Emphasis, Halftone, Dropout color (None /Red /Green /Blue /White / Saturation /Custom), sRGB output, Split image, De-Skew, Edge filler,
Connector shap Image processir	ng functions nents	Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, De-Screen, Emphasis, Halftone, Dropout color (None /Red /Green /Blue /White / Saturation /Custom), sRGB output, Split image, De-Skew, Edge filler, Vertical streaks reduction, Cropping, Dither, Static threshold AC 100 to 240 V ±10% Operating: 17 W or less Sleep mode: 1.1 W or less
Connector shap Image processir Power requirem	ng functions nents otion	Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, De-Screen, Emphasis, Halftone, Dropout color (None /Red /Green /Blue /White / Saturation /Custom), sRGB output, Split image, De-Skew, Edge filler, Vertical streaks reduction, Cropping, Dither, Static threshold AC 100 to 240 V ±10% Operating: 17 W or less
Connector shap Image processir Power requiren Power consump Operating envir	ng functions nents otion	Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, De-Screen, Emphasis, Halftone, Dropout color (None /Red /Green /Blue /White / Saturation /Custom), sRGB output, Split image, De-Skew, Edge filler, Vertical streaks reduction, Cropping, Dither, Static threshold AC 100 to 240 V ±10% Operating: 17 W or less Sleep mode: 1.1 W or less Auto standby (OFF) mode: 0.15 W or less Temperature: 5 to 35 °C (41 to 95 °F)
Connector shap Image processir Power requiren Power consump Operating envir	ng functions nents otion ronment	Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, De-Screen, Emphasis, Halftone, Dropout color (None /Red /Green /Blue /White / Saturation /Custom), sRGB output, Split image, De-Skew, Edge filler, Vertical streaks reduction, Cropping, Dither, Static threshold AC 100 to 240 V ±10% Operating: 17 W or less Sleep mode: 1.1 W or less Auto standby (OFF) mode: 0.15 W or less Temperature: 5 to 35 °C (41 to 95 °F) Relative humidity: 20 to 80% (Non-condensing)
Connector shap Image processin Power requiren Power consump Operating envir Dimensions: Wid	ng functions nents otion ronment ith x Depth x Height*8	Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, De-Screen, Emphasis, Halftone, Dropout color (None /Red /Green /Blue /White / Saturation /Custom), sRGB output, Split image, De-Skew, Edge filler, Vertical streaks reduction, Cropping, Dither, Static threshold AC 100 to 240 V ±10% Operating: 17 W or less Sleep mode: 1.1 W or less Auto standby (OFF) mode: 0.15 W or less Temperature: 5 to 35 °C (41 to 95 °F) Relative humidity: 20 to 80% (Non-condensing) 290 x 146 x 130 mm (11.41 x 5.74 x 5.11 in.) 2.9 kg (6.4 lb) PaperStream IP driver (TWAIN/TWAIN x64/ISIS), PaperStream Capture, Software Operation Panel, Error Recovery Guide, ScanSnap Manager for fi Series*9, Scan to Microsoft SharePoint*9, ABBYY FineReader for
Connector shap Image processin Power requirem Power consump Operating envir Dimensions: Wid Weight	ng functions nents otion ronment Ith x Depth x Height*8 are / drivers	Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, De-Screen, Emphasis, Halftone, Dropout color (None /Red /Green /Blue /White / Saturation /Custom), sRGB output, Split image, De-Skew, Edge filler, Vertical streaks reduction, Cropping, Dither, Static threshold AC 100 to 240 V ±10% Operating: 17 W or less Sleep mode: 1.1 W or less Auto standby (OFF) mode: 0.15 W or less Temperature: 5 to 35 °C (41 to 95 °F) Relative humidity: 20 to 80% (Non-condensing) 290 x 146 x 130 mm (11.41 x 5.74 x 5.11 in.) 2.9 kg (6.4 lb) PaperStream IP driver (TWAIN/TWAIN x64/ISIS), PaperStream Capture, Software Operation Panel, Error Recovery Guide, ScanSnap Manager
Connector shap Image processin Power requiren Power consump Operating envir Dimensions: Wid Weight Included softwa	ng functions nents otion ronment Ith x Depth x Height*8 are / drivers	Multi image output, Automatic color detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, De-Screen, Emphasis, Halftone, Dropout color (None /Red /Green /Blue /White / Saturation /Custom), sRGB output, Split image, De-Skew, Edge filler, Vertical streaks reduction, Cropping, Dither, Static threshold AC 100 to 240 V ±10% Operating: 17 W or less Sleep mode: 1.1 W or less Auto standby (OFF) mode: 0.15 W or less Temperature: 5 to 35 °C (41 to 95 °F) Relative humidity: 20 to 80% (Non-condensing) 290 x 146 x 130 mm (11.41 x 5.74 x 5.11 in.) 2.9 kg (6.4 lb) PaperStream IP driver (TWAIN/TWAIN x64//ISIS), PaperStream Capture, Software Operation Panel, Error Recovery Guide, ScanSnap Manager for fi Series*9, Scan to Microsoft SharePoint*9, ABBYY FineReader for ScanSnap™*9, Scanner Central Admin Agent

fi-7030

Capable of scanning documents that exceed Legal sheets in length. Long page scanning supports documents with a length of up to 5,588 mm (220 in.) when the resolution is set to 200 dpi or less. Actual scanning speeds are affected by data transmission and software processing times. Indicated speeds are from using IPEC compression. Indicated speeds are from using IFF CUIT Group 4 compression. Maximum capacity varies, depending upon paper weight. Selectable maximum density may vary depending on the length of scanned document. When scanning at high resolution (over 600dpi), some limitations apply to the size of the document that could be scanned, depending on system environment.

*8 *9

system environment. Excluding the ADF paper chute and Stacker. The software can be downloaded from the website designated in the Setup DVD-ROM.

	Description	Parts number	Comments		
	Carrier Sheet	PA03360-0013	Each package contains 5 carrier sheets. It is recommended that each carrier sheet be replaced after it has been used for 500 scans.		
	2D Barcode for PaperStream	PA43404-A433	This option enables the scanner to recognize 2D Barcode. (PDF417, QR code, Data Matrix, Aztec Code)		

■Consumables

	Description		Parts number	Comments	
	Roller Set	Brake Roller	- PA03706-0001	Lifetime: Every 200,000 sheets or one year. These rollers separate documents as they are being fed into the scanner.	
	Koller Set	Pick Roller		Lifetime: Every 200,000 sheets or one year. These rollers feed documents into the scanner.	

Trademarks

- ABBYY and FineReader are trademarks of ABBYY Software, Ltd. which may be registered in some jurisdictions. ISIS is a registered trademark of EMC Corporation in the United States. Microsoft, Windows, Windows Server, Windows Vista and SharePoint are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. * Other company names and product names are the registered trademarks or trademarks of the respective companies.
- Visit the fi Series web site for ordering and purchasing information

http://imagescanner.fujitsu.com



 Be sure to carefully read all safety precautions prior to using this product and use this device as instructed be sure to the out start, present price of a start, present price of the product of the product under such conditions may result in electrical shock, fire or damage to this product.
Be sure to limit the use of this product to listed power ratings.



PFU Limited, a Fujitsu company, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.



fi-7030 Technical Specifications

Description

